





THERM-X-TROL®

Water Heater Expansion Tanks Featuring Antimicrobial Protection

Specifications



ST-5, ST-8, ST-12



ST-25V through ST-210V

Model Number	Tank Volume (Gallons)	Max. Accept. Volume (Gallons)	A Diameter (Inches)	B Height (Inches)	System Connection	Shipping Weight (lbs.)
ST-5	2.0	0.9	8	13	¾ NPTM	5
ST-8	3.2	1.9	9	15	¾ NPTM	7
ST-12	4.4	3.2	11	15	¾ NPTM	9
ST-25V	10.3	10.3	15	19	¾ NPTF	23
ST-30V	14.0	11.3	15	24	¾ NPTF	25
ST-42V	20.0	11.4	15	32	¾ NPTF	33
ST-60V	34.0	34.0	22	30	1¼ NPTF	61
ST-80V	44.0	33.9	22	36	1¼ NPTF	69
ST-180V	62.0	34.1	22	47	1¼ NPTF	92
ST-200V	81.0	33.2	22	56	1¼ NPTF	103
ST-210V	86.0	46.4	26	47	1¼ NPTF	123

Stainless Steel System Connection.

Maximum Operating Temperature: 200°F.

Maximum Working Pressure 150 psig. Factory Pre-charge: 50 PSIG.

THERM-X-TROL® Quick Sizing Charts

Maximum Temperature Setting 140°F

Water Heater Size (gals.)	Static Supply Pressure (psig)		
	40	60	80
40	ST-5	ST-5	ST-5
50	ST-5	ST-5	ST-5
60	ST-8	ST-8	ST-8
80	ST-8	ST-8	ST-12
120	ST-12	ST-12	ST-25V

Maximum Temperature Setting 160°F

Water Heater Size (gals.)	Static Supply Pressure (psig)		
	40	60	80
40	ST-5	ST-5	ST-8
50	ST-5	ST-8	ST-8
60	ST-8	ST-8	ST-12
80	ST-8	ST-12	ST-25V
120	ST-12	ST-25V	ST-25V

Maximum Temperature Setting 180°F

Water Heater Size (gals.)	Static Supply Pressure (psig)		
	40	60	80
40	ST-8	ST-8	ST-8
50	ST-8	ST-8	ST-12
60	ST-8	ST-12	ST-25V
80	ST-12	ST-25V	ST-25V
120	ST-25V	ST-25V	ST-25V

Sizing based on: 40°F incoming water temperature; 150 psi T&P safety relief valve; Precharge equal to static supply pressure. For larger applications: Visit amtrol.com, download the AMTROL App or contact Technical Support at 401.535.1216.



©2014 Amtrol Inc.



MC 8520 (08/14)