





WELLXTROL

Next Generation Well Tanks Featuring Antimicrobial Protection



Specifications

| Model Number | Tank Volume (Gallons) | Max. Acceptance Factor | Dimensions | | System Conn. (Inches) | Drawdown (Gallons) | | | Shipping Weight (lbs.) |
|--------------|-----------------------|------------------------|---------------------|-------------------|-----------------------|--------------------|--------------|--------------|------------------------|
| | | | A Diameter (Inches) | B Height (Inches) | | 30/50 (psig) | 40/60 (psig) | 50/70 (psig) | |
| WX-101 | 2.0 | 0.45 | 8 | 13 | ¾ NPTM | 0.6 | 0.6 | 0.5 | 5 |
| WX-102 | 4.4 | 0.55 | 11 | 15 | ¾ NPTM | 1.4 | 1.2 | 1.0 | 9 |
| WX-103 | 6.7 | 0.43 | 11 | 22 | ¾ NPTM | 2.4 | 2.0 | 1.8 | 15 |
| WX-104 | 10.3 | 1.00 | 15 | 18 | 1 NPTM | 3.2 | 2.8 | 2.4 | 20 |
| WX-200 | 14.0 | 0.81 | 15 | 22 | 1 NPTM | 4.3 | 3.8 | 3.3 | 22 |
| WX-201 | 14.0 | 0.81 | 15 | 25 | 1 NPTF | 4.3 | 3.8 | 3.3 | 25 |
| WX-202 | 20.0 | 0.57 | 15 | 32 | 1 NPTF | 6.2 | 5.4 | 4.7 | 32 |
| WX-202XL | 26.0 | 0.44 | 15 | 39 | 1 NPTF | 8.0 | 7.0 | 6.1 | 39 |
| WX-203 | 32.0 | 0.35 | 15 | 47 | 1 NPTF | 9.9 | 8.6 | 7.6 | 47 |
| WX-205 | 34.0 | 1.00 | 22 | 30 | 1 ¼ NPTF | 10.5 | 9.1 | 8.0 | 57 |
| WX-250 | 44.0 | 0.77 | 22 | 36 | 1 ¼ NPTF | 13.6 | 11.8 | 10.4 | 65 |
| WX-251 | 62.0 | 0.55 | 22 | 47 | 1 ¼ NPTF | 19.2 | 16.6 | 14.6 | 87 |
| WX-255 | 81.0 | 0.41 | 22 | 57 | 1 ¼ NPTF | 25.0 | 21.7 | 19.1 | 109 |
| WX-302 | 86.0 | 0.54 | 26 | 47 | 1 ¼ NPTF | 26.6 | 23.0 | 20.3 | 106 |
| WX-350 | 119.0 | 0.39 | 26 | 62 | 1 ¼ NPTF | 36.8 | 31.9 | 28.1 | 146 |

Stainless Steel System Connection.

Maximum Working Pressure: All models: 150 psig. Factory Precharge: 38 psig.

Drawdown can be affected by various ambient and system conditions, including temperature and pressure.

Well-X-Trol® ESP Quick Sizing Table

| Pump Discharge Rate (Approx. GPM) | Pumps Up To 3/4 hp & 1 Minute Run Time | | | Pumps Over 3/4 hp & 2 Minute Run Time | | |
|--------------------------------------|--|------------|------------|---------------------------------------|------------|------------|
| | 30/50 psig | 40/60 psig | 50/70 psig | 30/50 psig | 40/60 psig | 50/70 psig |
| 5 | WX-202 | WX-202 | WX-202 | WX-205 | WX-205 | WX-250 |
| 7 | WX-202XL | WX-203 | WX-203 | WX-250 | WX-251 | WX-251 |
| 10 | WX-203 | WX-205 | WX-250 | WX-251 | WX-255 | WX-302 |
| 12 | WX-250 | WX-250 | WX-251 | WX-255 | WX-255 | WX-350 |
| 15 | WX-250 | WX-251 | WX-251 | WX-302 | WX-350 | WX-350 |
| 20 | WX-251 | WX-255 | WX-302 | WX-350 | WX-255 (2) | WX-302 (2) |
| 25 | WX-255 | WX-302 | WX-350 | WX-255 (2) | WX-302 (2) | WX-350 (2) |
| 30 | WX-302 | WX-350 | WX-350 | WX-302 (2) | WX-350 (2) | WX-302 (3) |
| 35 | WX-350 | WX-350 | WX-255 (2) | WX-350 (2) | WX-350 (2) | WX-350 (3) |
| 40 | WX-350 | WX-255 (2) | WX-302 (2) | WX-350 (2) | WX-302 (3) | WX-350 (3) |

The Effective System Protection (ESP) reduces system wear and energy consumption by keeping pump starts to a minimum.

Larger Tank = Fewer Cycles = Longer Tank and Pump Life.



1400 Division Road, West Warwick, RI 02893 USA T: 800.426.8765 www.amtrol.com

© 2021 Worthington Industries Inc.



MC7025 (07/21)