



### 150 PSIG Working Pressure

#### Construction


Shell	ASME Approved Steel
Diaphragm	Heavy Duty Butyl/EPDM
System Connection	NPTF <sup>1</sup> Malleable Iron Center NPTF <sup>2</sup> Malleable Iron Bottom NPTM <sup>3</sup> Steel Pipe, Top Offset
Finish	Red Oxide Primer
Air Valve	Schrader Valve w/EPDM Seats
Factory Precharge	12 PSIG (.8 bar)

#### Performance

Maximum Operating Temperature	240°F (115°C)
Maximum Working Pressure	150 PSIG (10.3 bar)
Warranty	3-Years

#### Application

- For use in closed, non-potable hydronic heating and chilled water systems.
- Designed to meet all ASME Code Section VIII, Division 1 standards.
- Available with optional sight glass and seismic restraints.
- Suitable in propylene glycol applications with mixtures up to 50%.
- Deep drawn models are lighter, stronger and more compact than traditional head and shell construction.




#### Deep Drawn ASME Models

Model Number	Tank Volume		Max. Accept. Volume		A Tank Diameter		B Tank Height		Sys. Conn	Shipping Weight	
	Gal	Lit	Gal	Lit	In	mm	In	mm		In	Lbs
AX-15V-DD	8.6	33	3.2	12.1	12	305	22	559	3/4" <sup>1</sup>	42	19
AX-20V-DD	16.5	63	11.3	43	15	381	25	636	3/4" <sup>1</sup>	48	22
AX-40V-DD	23	88	11.3	43	15	381	33	838	3/4" <sup>1</sup>	96	44

#### Head & Shell ASME Models

Model Number	Tank Volume		Max. Accept. Volume		A Tank Diameter		B Tank Height		Sys. Conn	Shipping Weight	
	Gal	Lit	Gal	Lit	In	mm	In	mm		In	Lbs
AX-60V	33.6	127.2	11.3	42.8	16	356	45	1143	1/2" <sup>1</sup>	104	47
AX-80V	44.4	168.1	22.6	85.5	24	610	29	737	1" <sup>1</sup>	171	78
AX-100V	55.7	211.8	22.6	85.5	24	610	34	863	1" <sup>1</sup>	190	86
AX-120V	68.0	257.4	34.0	128.7	24	610	47	1194	1 <sup>2</sup>	220	100
AX-144V	77.0	291.5	34.0	128.7	24	610	52	1321	1 <sup>2</sup>	255	116
AX-180V	90.0	340.7	34.0	128.7	24	610	60	1524	1 <sup>2</sup>	276	125
AX-200V	110.0	416.4	34.0	128.7	24	610	66	1676	1 <sup>2</sup>	300	136
AX-240V	132.0	500.0	46.0	174.0	30	762	58	1473	1 <sup>2</sup>	426	193
AX-260V	159.0	600.0	56.0	212.0	30	762	65	1651	1 1/4" <sup>3</sup>	467	212
AX-280V	211.0	800.0	84.0	318.0	30	762	82	2083	1 1/4" <sup>3</sup>	611	277



BOTTOM VIEW

#### Optional Seismic Restraints

Tank Diameter	Bolt Circle	Dim. E	Dim. F	Hole Size
B	D	E	F	G
12	12 3/4	2	2	9/16
16 1/4	14 3/4	2	2	9/16
24	18	2	2	9/16
30	27	3	3	3/4

All dimensions and weights are approximate.

Job Name _____	Notes _____
Engineer _____	_____
Contractor _____	_____
P.O. No. _____	_____
Sales Rep. _____	_____
Model No. _____	_____

