



THERM-X-SPAN®

Thermal Expansion Tanks: T-5A and T-12A

150 PSIG Working Pressure

Construction

Shell	Steel
Diaphragm	Heavy Duty Butyl
Liner	Polypropylene
Connection	Stainless Steel
Factory Precharge	40 PSIG (2.8 bar)

Performance

Maximum Operating Temperature	200°F (93°C)
Maximum Working Pressure	150 PSIG (10.3 bar)
Warranty	5-Year


Application

- For use in closed, potable water systems to control pressure build-up.
- Accepts expanded water as system temperature rises and returns hot water to system when demand occurs.
- Multiple units can be installed to accommodate larger systems.

In-Line Models

Model Number	Tank Volume		Max. Acceptance Factor	A Tank Diameter		B Tank Height		System Connection (NPTM)	Shipping Weight	
	Gal	Lit		In	mm	In	mm		Lbs	Kg
T-5A	2.0	8	.45	8	203	12	305	¾	5	2
T-12A	4.4	17	.59	11	279	15	381	¾	9	4

All dimensions and weights are approximate.



Job Name _____	Notes _____
Engineer _____	_____
Contractor _____	_____
P.O. No. _____	_____
Sales Rep. _____	_____
Model No. _____	_____

